

DGS Xpress LAM XL-1600C (1.63m/64") Full Auto Heat-Assist Cold Laminator

OPTIMUM PERFORMANCE

- + Hybrid laminator for booth laminating and cutting
- + Pneumatic nip gap adjustment ensures even pressure
- + Premium silicon roller ensures heavy-duty work and longer life
- + Adjustable setting for increased capacity and versatility

EASE OF USE

- + Simple adjustment tension
- + Light weight drop-in supply shafts with auto-grip for easy loading of materials
- + Fully adjustable nip-gap and pressure for precise application
- + Roll-to-Roll and Piece-to-Piece operation capacity

SAFETY

- + Foot switch for hands free operation
- + Laser safety eyes and 2 emergency stop buttons
- + CE, PSE



TECHNICAL SPECS

- + Max Laminating Width: (1630mm/64")
- + Max Laminating Thickness: (23mm/1")
- + Max Speed: Up to (6m/min 236"/min)
- + Max Temp: 60°C/140°F
- + Rollers: Silicon (110mm diameter)
- + Pressure/Height Adjust: Pneumatic
- + Heated Method: Infrared
- + Preheating Time: 5-10 min
- + Power Input: 1600w
- + KW/H: 0.5-0.8
- + Volt: 110/220v, 50/60Hz
- + Emergency Button: 2
- + Laser Eye: Yes







